











































K3/K4 PRODUCT DESK REFERENCE

T 800.728.7950 586.294.7950 | F 800.294.0067 586.294.0067 | college-park.com



	FOOT	MOUNTING	WEIGHT LIMIT	SIZES	IMPACT	BUILD HEIGHT	WEIGHT**	WTY	L-CODE†	ENVIROSHIELD	HEEL HEIGHT
VERT SHOCK	 AVIATOR	Endo (IP)	275 lbs (21-25 cm) 330 lbs (26-30 cm)	21-30 cm		6.5 in	979 g	3	L5987 PDAC APPROVED	 standard	0.38 in
	 VOYAGER	Endo (IP)	275 lbs (21-25 cm) 330 lbs (26-30 cm)	21-30 cm		7.5 in	1,174 g	3	L5987 + L5984 PDAC APPROVED	 standard	0.38 in
INTEGRATED SPRING TECHNOLOGY	 SOLEUS	Endo (4-hole)	220 lbs (21-24 cm) 250 lbs (25-26 cm) 275 lbs (27-30 cm)	21-30 cm		6.4 in (21-24 cm) 7.2 in (25-26 cm) 7.6 in (27-30 cm)	667 g	3	L5981 PDAC APPROVED	 narrow & wide	0.38 in
	 VELOCITY	Endo (IP)	250 lbs (25-26 cm) 275 lbs (27-30 cm)	25-30 cm		4.7 in (25-26 cm) 5.2 in (27-30 cm)	631 g	3	L5981 + L5986	 narrow & wide	0.38 in
TRI-AXIAL	 TERRAIN	Endo (IP)	330 lbs (21-25 cm) 365 lbs (26-30 cm)	21-30 cm		3.4 in (21-25 cm) 3.6 in (26-30 cm)	815 g	3	L5981 + L5986 PDAC APPROVED	 standard	0.38 in
	 VENTURE	Endo (IP) Exo (ALX)	250 lbs (21-24 cm) 275 lbs (25-30 cm)*	21-30 cm		2.5-2.7 in (IP) 5.0-5.2 in (ALX)	585 g	3	L5981 + L5986	 narrow & wide	0.38 in
	 TRUSTEP	Endo (IP) Exo (ALX)	330 lbs (Endo) 352 lbs (Exo)	22-31 cm		3.5 in (IP) 6.0 in (ALX)	678 g	3	L5979 PDAC APPROVED	 narrow & wide	0.5 in
	 TRIBUTE	Endo (IP)	220 lbs	21-30 cm		2.4 in	529 g	2	L5979 PDAC APPROVED	 standard narrow & wide	0.38 in
CARBON+ TORSION	 ORBIT	Endo (IP)	330 lbs	21-30 cm		3.7 in (21-25 cm) 3.9 in (26-30 cm)	895 g	3	L5981 + L5984 PDAC APPROVED	 standard	0.38 in
CARBON	 HORIZON HD	Endo (IP)	330 lbs (21-25 cm) 365 lbs (26-30 cm)	21-30 cm		2.3 in	559 g	3	L5981 PDAC APPROVED	 standard	0.38 in
K3 CURVED HYDRAULIC	 ODYSSEY_{K3}	Endo (IP)	275 lbs	21-30 cm		3.0 in	749 g	3	L5981 + L5968 PDAC APPROVED	 standard	0.38 in
ADJUSTABLE HEEL	 ACCENT	Endo (IP) D.Pylon (DP)	220 lbs (21-24 cm) 250 lbs (25-28 cm)	21-28 cm		3.3-3.9 in (IP) 7.8-8.0 in (4-H) 7.8-8.1 in (male) 8.3-8.5 in (female)	608 g (IP) 761 g (DP) w/pylon	2	L5981+ L5986+ L5990	 narrow & wide	2.0 in (range)
PEDIATRIC	 SCOUT	Lam Adapter Pyramid Receiver Exo (ALX)	55 lbs (13-15 cm) 100 lbs (16-18 cm) 132 lbs (19-22 cm)	13-22 cm		1.9-2.1 in (Lam Adpt) 1.8-2.1 in (Pyramid) 2.1-2.4 in (Receiver) 4.1-4.3 in (ALX)	183-360g [†]	1	L5981 PDAC APPROVED	 standard	0.24 in (13-15cm) 0.25 in (16-18 cm) 0.38 in (19-22 cm)
	 TRUPER	Endo (IP) Exo (ALX)	100 lbs (16-18 cm) 132 lbs (19-21 cm)	16-21 cm		2.1-2.4 in (IP) 4.3-4.6 in (ALX)	215-314 g (16-21 cm)	1	L5979 PDAC APPROVED	 standard	0.25 in

* Low impact only

[†]13-22 cm, including Pyramid Adapter and Enviroshell
^{**}26 cm, including Enviroshell

Caucasian, Tan, Brown, Jet Black

	KNEE	K-LEVEL	WEIGHT LIMIT	WEIGHT	OVERALL HEIGHT	DOME TO KNEE CENTER	FLEXION RANGE	L-CODE†	WTY
MICRO-PROCESSOR	 ICON	K2-K4	330 lbs	1530 g	10.5 in	0.67 in	130°	L5828+ L5845+ L5848+ L5850+ L5856+ L5925 PDAC APPROVED	3 (3 year extended warranty available)
HYDRAULIC	 CAPITAL	K3-K4	330 lbs	1010 g (pylon) 1020 g (pyramid)	9.0 in	0.67 in	130°	L5828+ L5845+ L5850+ L5925	3
PNEUMATIC	 VICTOR	K3	275 lbs	710 g	8.0 in	1.1 in	145°	L5822+ L5845+ L5850	2

† The listing of codes with these products should not be construed as a guarantee for coverage or payment. Ultimate responsibility for the coding of services/products rests with the individual practitioner.

K2 PRODUCT DESK REFERENCE

T 800.728.7950 586.294.7950 | F 800.294.0067 586.294.0067 | college-park.com



	FOOT	MOUNTING	WEIGHT LIMIT	SIZES	IMPACT	BUILD HEIGHT	WEIGHT**	WTY	L-CODE†	ENVIROSHIELD	HEEL HEIGHT
K2 CURVED HYDRAULIC		ODYSSEY K2	Endo (IP)	220 lbs (21-24 cm) 300 lbs (25-30 cm)	21-30 cm	 3.1 in (21-24 cm) 3.3 in (25-30 cm)	744 g	2	L5972 + L5968		0.38 in
		TERRAIN iW	Endo (IP)	220 lbs (21-24 cm) 300 lbs (25-30 cm)	21-30 cm	 2.5 in (21-24 cm) 2.7 in (25-26 cm) 2.8 in (27-30 cm)	645 g	2	L5972 + L5986 PDAC APPROVED		0.38 in
K2		CELSUS	Endo (IP)	220 lbs (21-24 cm) 300 lbs (25-30 cm)	21-30 cm	 2.2 in (21-24 cm) 2.5 in (25-26 cm) 2.6 in (27-30 cm)	526 g	2	L5972 + L5986		0.38 in
		TEMPO	Endo (IP)	300 lbs (21-24 cm) 330 lbs (25-30 cm)	21-30 cm	 2.2 in (21-24 cm) 2.5 in (25-26 cm) 2.6 in (27-30 cm)	500 g	2	L5972 PDAC APPROVED		0.38 in
		BREEZE	Endo (IP)	220 lbs (21-25 cm) 275 (26-30 cm)	21-30 cm	 2.4 in (21-25 cm) 2.6 in (26-30 cm)	523 g (25 cm)	2	L5972		0.38 in
K2 VACUUM		CELSUS iVT	Endo (IP)	220 lbs (21-24 cm) 300 lbs (25-30 cm)	21-30 cm	 2.2 in (21-24 cm) 2.5 in (25-26 cm) 2.6 in (27-30 cm)	652 g	2	L5972 + L5986 + L5781		0.38 in
		TEMPO iVT	Endo (IP)	300 lbs (21-24 cm) 330 lbs (25-30 cm)	21-30 cm	 2.2 in (21-24 cm) 2.5 in (25-26 cm) 2.6 in (27-30 cm)	626 g	2	L5972 + L5781		0.38 in
STUBBIES		SIDEKICKS	Endo (IP)	275 lbs	ONE SIZE	 2.3 in	422 g	2	L5972 + L5986	No Enviroshell	0 in

* Low impact only

** 26 cm, including Enviroshell

† Caucasian, Tan, Brown, Jet Black

	KNEE	K-LEVEL	WEIGHT LIMIT	WEIGHT	OVERALL HEIGHT	DOVE TO KNEE CENTER	FLEXION RANGE	L-CODE†	WTY	
POLYCENTRIC		AURA	K2	300 lbs	665 g	6.32 in	0.65 in	135°	L5611+ L5845+ L5850+ L5925	2
FRICTION BRAKE		GUARDIAN	K2	275 lbs	533 g	5.2 in	1.0 in	145°	L5812+ L5845+ L5850+ L5925	2

‡ The listing of codes with these products should not be construed as a guarantee for coverage or payment. Ultimate responsibility for the coding of services/products rests with the individual practitioner.

ALSO AVAILABLE



CEU COURSES AND EDUCATION

College Park Campus offers free education, training, and certification opportunities for prosthetists and other healthcare professionals.

Enroll today:
www.college-park.com/education

ENDO COMPONENTS

College Park components are highly engineered for noise abatement and strength.



TORSION ADAPTERS

Made of titanium and stainless steel, this durable component is easily adjustable for prosthetists. It offers a maximum of 20° of internal and external rotation. WITH Made of titanium and stainless steel, this adjustable component offers up to 20° of internal and external rotation.



FREE SHIPPING!

Order online to receive free 2-day shipping options! We can directly bill your College Park account.



BE THE FIRST TO KNOW

Sign up for the email newsletter to receive our latest news, events, promotions, and product releases!



LET'S CONNECT

We invite you to follow College Park on social media for helpful resources, inspiring stories, and more.

